



Wheel-Type Tandem Disc Harrows



When it comes to sheer versatility and performance, there's never been a better choice than the Taylor-Way 351 Tandem Disc Harrow. With nearly 40 options in narrow and wide frame configurations, the 351 is engineered with smart features, easy adjustments and customizing extras.

The rigid, tubular frame design creates the stability and weight you need to achieve outstanding cutting and leveling even in the toughest soil conditions. High carbon, square 1-1/8" gang axles are built to deliver maximum penetration and durability. Machined, ductile spacer spools combined with 7-1/2", 9" or combination disc spacing maintain clearance and optimum pulverization.

Available in Standard or Flex Bearing Hanger Models

<u>Width</u>	<u>Discs</u>			<u>Weight*</u>	<u>DB Hp</u>
	<u>Spacing</u>	<u>Size</u>	<u>Qty</u>		
Narrow Frame Models					
9' 3"	7½"	20"	28	3932 lbs	55
9' 3"	9"F / 7½"R	20"	26	3890 lbs	55
9' 4"	9"	20"	24	3842 lbs	55
10' 5"	7½"	20"	32	4144 lbs	60
10' 5"	9"F / 7½"R	20"	30	4120 lbs	60
10' 9"	9"	20"	28	4096 lbs	60
11' 6"	7½"	20"	36	4356 lbs	65
11' 6"	9"F / 7½"R	20"	34	4356 lbs	65
12' 2"	9"	20"	32	4350 lbs	65
Wide Frame Models					
12' 10"	7½"	20"	40	4858 lbs	70
13' 7"	9"	20"	36	4737 lbs	70
14' 0"	7½"	20"	44	5112 lbs	75
14' 0"	9"F / 7½"R	20"	40	4925 lbs	75
14' 10"	9"	20"	40	4997 lbs	75
15' 2"	7½"	20"	48	5366 lbs	80
15' 2"	9"F / 7½"R	20"	44	5185 lbs	80
16' 3"	9"	20"	44	5245 lbs	80
16' 4"	7½"	20"	52	5620 lbs	85
16' 4"	9"F / 7½"R	20"	48	5433 lbs	85

***Note:** Weights are for Standard Bearing Hanger Models